



Display size	22" (55,88 cm) WIDE
Panel Type	Active Matrix TFT
Brightness	300 cd/m² (typ.)
Contrast (typ.)	1000:1
X-Contrast (dyn.)	-
Pixel pitch	0,282(H) x 0,282(V) mm
Resolution (H x V)	WSXGA+ 1680 x 1050
Response time	5 ms (typ.)
View angles (CR>10)	H/V 170°/160°
View angles (CR>5)	
Display colors	16,7 Mio colors
Display Surface	Anti-Glare
Input 1	VGA, Audio
Input 2	
Input 3	
Headphone	
Speakers	2 x 1,5W
Supply	AC 100~240V, 50~60Hz
Consumption	On: 40 W Stand-by: < 2 W Off: < 1 W
Operation Temp/Hum	5 ~ 40°C 20% ~ 80%
Dimension (W*D*H)	510 x 202 x 424 mm
Net weight	4,9 kg
Tilt	0°~ 20°
Kensington Lock	✓
VESA mounting	VESA Standard, 100mm
On screen display	EN,TC,DE,FR,ES,IT,PT,NL,SC,JP,KR,RU
Safety	CD,CB,Nemko-GS
Emission	TCO03
Emission Power saving	TCO03 EnergyStar
Power saving	EnergyStar
Power saving Extras 1	EnergyStar
Power saving Extras 1 Extras 2	EnergyStar



trademarks and/or registered trademarks of their respective manufacturers and companies. Screenshots are simulated. © HANNspree Europe GmbH. Information in this document is subject to change without notice. All brand, product, service names and logos are